

## 1/4-Inch Color Mini Dome CCD Camera

**CM-D1000**

### Feature

- For Use With 1/4" Format Camera
- Min. Illumination 1 Lux at F2.5
- With 380 TV Lines Horizontal Resolution
- Auto Gain Control
- Automatic white balance



### Specification

General	
Pick up device	1/4" interline transfer CCD
Total Pixels	NTSC:537(H) x 505(V) / PAL:537(H) x 597(V)
Effective Pixels	NTSC:510(H) x 492(V) / PAL:500(H) x 582(V)
Resolution	With 380 TV lines
Sync. System	Internal Sync.
Scanning System	NTSC: 525 Lines / 60 Fields ; PAL: 625 Lines / 50 Fields
S/N Ratio	More than 48 dB
Electronic Shutter	Auto/manual 1/60 (1/50) ~1/100,000 sec.
Min. Illumination	1 lux / F2.5
Video Output	Composite 1.0 Vp-p / 75 ohm
White Balance	ATW (Auto Tracing White Balance)
Automatic Gain Control	ON
View Angle	H:85° V:64°
Frequency	
Horizontal	NTSC: 15.734 KHz ; PAL: 15.625 KHz
Vertical	NTSC: 59.94Hz ; PAL: 50Hz
Lens Type	Board Lens 2.5mm (1/3" f:2.5 F2.5)
Electrical	
DC power Source	DC12V
Power Consumption	1W (Max)
Current	85mA (Max) / DC12V
Weight	N.W./G.W.: 0.07kg / 0.11kg
Dimension	60(Diameter) x 46(H)mm
Operation Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-20 to 70°C (-4 to 158 °F)

### Dimension

