

Outdoor Color CCD IP camera

CM-I1010

Feature

Network function

- MPEG-4 & M-JPEG Compression
- Support MPEG-4 / M-JPEG dual bit streaming at the same time(PC / 3G)
- Schedule Recording, easier direct record at remote site
- Pre- and Post Alarm recording and message Delivery (E-mail / FTP)
- JPG file snapshot function, time/date display
- AVI file record function, time/date display
- Motion detection (3 areas) and record function
- Two Way Audio Support
- Provide remote IE viewing function

Camera Body

- With 1/3" Format SONY CCD
- Vari-Focal Lens Adjustable Externally
- Auto IRIS Lens Built-in
- Built-in removable IR Cut Filter Built-in, accurate focus for Day & Night
- Aluminum Alloy Housing for Better Heat Dissipation
- Class IP67 Weatherproof



Specification

| | |
|---------------------|--|
| Video (Compression) | CM-I1010 |
| Compression method | MPEG-4 / M-JPEG |
| Resolution | Full D1 (720 x 480 in NTSC, 720 x 576 in PAL) CIF (352 x 240 in NTSC, 352 x 288 in PAL) QCIF (160 x 120 in NTSC, 176 x 144 in PAL) |
| Bit Rate | 16 K ~1M bps |
| Image Frame Rate | 30 fps at full D1 resolution (NTSC) 25 fps at full D1 resolution (PAL) |
| Audio | |
| Microphone | 16k~48kHz Mono, MP2, AMR |
| Output format | 16k~48kHz stereo, Mono, PCM |
| Remote Control | |
| Serial Port | RS-485: half duplex, terminal block |
| Network | |
| LAN Port | Ethernet (10/100Base-T), RJ45 connector |
| Protocol | TCP, UDP,HTTP, DHCP, PPPoE, RTP, RTSP, FTP, SMTP |
| Software | |
| Web Browser | Microsoft Internet Explorer 6.0 or above |
| Security | Password protection: configured by the administrator |
| General | |
| Pick up device | 1/3" interline transfer CCD |
| Total Pixels | NTSC:537(H) x 505(V) / PAL:537(H) x 597(V) |
| Effective Pixels | NTSC:510(H) x 492(V) / PAL:500(H) x 582(V) |
| Resolution | 420 TV lines |
| Sync. System | 2:1 Internal |
| Scanning System | NTSC: 525 Lines / 60 Fields ; PAL: 625 Lines / 50 Fields |
| S/N Ratio | More than 48 dB (AGC OFF) |
| Electronic Shutter | Auto 1/60 (1/50) ~1/100,000 sec. |
| Min. Illumination | 0.3 lux color / F2.0 |
| IR Distance | 25M (40pcs IR LED) |
| IR Trigger | 3.1lux / 3.7lux IR ON / OFF |
| Lens Type | Vari Focal Lens 9-22mm / F1.6 |
| Power | |
| Power Requirement | DC12V |
| Power Consumption | 4.8W~12W |
| Operating | |
| Temperature | -10 ~50 Ċ (14 ~122 ƒ) |

Dimension

