

1/3" IR Color CCD Camera

CM-T7300

Feature

- Metallic housing / outdoor (IP66)
- DC 12V / IR distance 12 M
- 380 TVL /Board lens : 4.3



Specification

	CM-T7300
Video System	NTSC / PAL
Pick up device	1/3" image sensor interline transfer CCD
Total Pixels	NTSC : 512(H) x 492(V) PAL :512(H) 582(V)
Effective Pixels	NTSC : 492(H) x 474(V) PAL :492(H) 564(V)
Resolution	380 TV lines
Sync. System	Internal Sync.
Scanning System	NTSC: 525Lines / 60Fields ; PAL : 625Lines / 50Fields
S/N Ratio	More than 48 dB(AGC OFF)
Electronic Shutter	1/60-1/100,000 sec. ; 1/50-1/100,000 sec.
Min. Illumination	0.15 lux color / F2.0 / 0 Lux with IR / F2.0
Video Output	1.0 Vp-p / 75 ohm composite
Scanning System	NTSC:15.734 Khz ; PAL:15.625 Khz
Gamma Correct	0.45
White Balance Control	Auto
Lens Mount Type	Board Lens : 4.3mm
DC power Source	DC12V
Dimension	50mm (Diameter) x 75(H)mm
Operation Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)

Dimension

