

16CH 480FPS Standalone DVR

CX-F6154

Feature

- High level specification with elegant design and jog/shuttle
- Control recording resolution / quality / frame rate by each camera
- USB mouse supported
- LIVE screen editing / Digital zoom / call monitor supported
- Event / Panic / Schedule record / optimized record mode supported
- Diversified search by Time / Calendar / Event
- Diversified backup by USB2.0 and DVD-RW
- Convenient backup by AVI file
- Support DDNS / NTP / E-MAIL / CALLBACK functions
- DISK ID, S.M.A.R.T functions, Real-time disk health check
- Multi-Languages supported
- Intensive security function by chosen AUTHORITY
- Diversified network program by LIVE / SEARCH / PTZ / CMS / AGENT



Specification

Model	CX-F6154
System	NTSC / PAL Manual switch
Input	16 CH input 1.0Vp-p, 75ohm unbalanced (BNC Type)
Output	1.0Vp-p, 75ohm unbalanced BNC (MainX1 / Call monitor X 2) / VGA / BNC x 16 video looping out
S/N Ratio	More than 48dB
Color	16.7 Million
Monitoring Method	
Display Screen	1 / 4 / 9 / 16
Zoom	2 x 2 zoom for live
Sequence Display	Available
Display Resolution	NTSC:720(H)x 480(V);PAL: 720(H) x 576(V)
Display Rate	480 frame per second (Real Time Display)
Recording / Play Function	
Recording Rate	D1: 120 / Half D1: 240 / CIF: 480 (NTSC) D1: 100 / Half D1: 200 / CIF: 400 (PAL)
Record Quality	Lowest / Low / Normal / High / Highest
Compressed Mode	MPEG-4
Recording Mode	Manual / Event(Motion detection, Alarm, Video loss) / Schedule
Playback Mode	Time search / Event search / Play directly / Calendar
Other Function	
Operation	Full Triplex
Motion Detect	Area division: 12 x12, on/off sector selectable Sensitivity adjustment in 5 steps
Network Function	TCP/IP with client software, IE (live view only)
Alarm Function	16 alarm In / 4 alarm Out: NC / NO+COM
Backup	Flash (USB 2.0) / DVD-RW / CD-RW / Network
RS485	PTZ Dome / Keyboard
Storage	Internal: up to 4 HDD
Audio	4 port input / 1 port output
VGA Output	15 pins female D-SUB
Mechanical	
IR Remote Controller	Standard
Shuttle Control Input	X 1
Power Supply	100~240Vac / 4A
Dimension	440(W) x 411.7(D) x 88(H)mm
Operating Temperature	5°C~+40 C (41 F~+104 F)
Operating Humidity	Less than 90%

Dimension

