



COMMITTED TO XCELLENCE™



## CX-H4191T

### 19" LCD-DVR Combo Monitor

CTX show you whole new way to use the DVR with simple, intuition and security. The integrated LCD/DVR combo with TOUCH function lets user has a comfortable experience of using DVR system and release from the many and diverse operation of keyboard and mouse. The reliable housing brings trust and high-end feeling to your desktop And the all-in-one design makes the installation more easily and saving space.

Triplex, MPEG-4 Compression Format, Audio Backup/ Audio Streaming, internal SATA Hard Disk Support, Graphic User Interface (GUI), Touch panel control/ Mouse (Optional) Support USB Backup / Firmware Update, Compact Size Multi – Language (English, Spanish, German, Chinese) , Lock the System & HDD by Password, Motion Detection, System Auto-recover after Power-cut throw the mouse and keyboard.

### Specification Overview:

LCD Diagonal Size	:	19"
Resolution	:	1280 x 1024 (SXGA)
Response Time	:	12ms (Typ.)
Contrast Ratio	:	500:1
Brightness	:	300 nit (cd/m <sup>2</sup> ),Typical
Viewing Angle (L/R)	:	140° / 130°
Display Color	:	16.2M
<b><u>DVR</u></b>		
Image System	:	PAL
Live-Time Resolution	:	720 x 576
Live time Display Rate	:	25 Frame/ Sec
Video Input	:	BNC x 4
Video Output	:	BNC x 1
Audio	:	Input RCA x 1 / Output RCA x 1
<b><u>RECORDING</u></b>		
Compression Type	:	MPEG-4
Recording Resolution	:	720 x 288 , 360 x 288
Recording Rate (CIF)	:	360 x 288 up to 100 PPS
Recording Rate (FIELD)	:	720 x 288 up to 25 PPS
Recording Mode	:	Manual /Schedule
<b><u>PLAY BACK &amp; SEARCH</u></b>		
Playback Speed	:	Fast Forward x2 x8 x16 x32 x64/ Fast Backward x32 Field by field playback /Slow motion Playback x1/2 x1/4
<b><u>OSD CONTROL INTERFACE</u></b>		
Title	:	8 Characters
On screen Display & Setup	:	Time / Date/ Setup Menu
Touch Panel	:	5-wires resistive
IE Browser	:	IE Interface for remote surveillance
<b><u>STORAGE &amp; BACKUP DEVICE</u></b>		
Internal HDD Support	:	SATA HDD x1
USB Backup	:	Yes
Audio Backup	:	Yes
<b><u>NETWORK</u></b>		
Ethernet	:	10Base -T/ 100Base-T
Ethernet Compression Format	:	MPEG-4
DDNS	:	Yes
Multi-View Client	:	5 Client available at the same time
Dimension	:	413.6 x 399.32 x 210 mm