

Video Server

CX-V1000

- MPEG-4 & M-JPEG Compression
- Support MPEG-4 / M-JPEG dual bit streaming at the same time (PC / 3G)
- Schedule Recording, easier direct record at remote site
- Pre- and Post Alarm recording and message Delivery (E-mail / FTP)
- JPG file snapshot function, time/date display
- AVI file record function, time/date display
- Event Recording with SD Card
- Motion detection (3 areas) and record function
- Two Way Audio Support
- Provide remote IE viewing function



Specification

Video (Compression)	CX-V1000
Compression method	MPEG-4 / M-JPEG
Horizontal Resolution	Full D1 (720 x 480 in NTSC, 720 x 576 in PAL) CIF (352 x 240 in NTSC, 352 x 288 in PAL) QCIF (160 x 120 in NTSC, 176 x 144 in PAL)
Bit Rate	16 K ~1M bps
Image Frame Rate	30 fps at full D1 resolution (NTSC) 25 fps at full D1 resolution (PAL)
Video Input	
Composite Input	BNC, 1.0Vp-p with 75 ohm loading, BNC connector
Video Output	
Composite Output	BNC, 1.0Vp-p with 75 ohm loading, BNC connector
Audio Input	
Format	16k~48kHz stereo, MP2, AMR
Audio Line Input	Unbalanced, 1.0Vpp, 1Vrms, 3.5mm Jack
Audio Output	
Format	16k~48kHz stereo, Mono, PCM
Audio Line Output	Unbalanced, 1.0Vpp, 1Vrms, 3.5mm Jack
Alarm	
Input	2, TTL, terminal block
Output	2, MOSFET, terminal block
Remote Control	
Serial Port	RS-485: half duplex, terminal block
External I/O	
Reset Button	Factory default
LED	System status
Network	
LAN Port	Ethernet (10/100Base-T), RJ45 connector
Protocol	TCP, UDP, IP, HTTP, DHCP, PPPoE, RTP, RTSP, FTP, SMTP
Software	
Web Browser	Microsoft Internet Explorer 6.0 or above
PTZ Protocol	Pelco-P, Pelco-D
Security	Password protection: configured by the administrator
Power	
Power Requirement	DC12V ± 10%
Power Consumption	4.5W~5.5W
Weight	N.W.:/G.W.: 0.4kg / 0.72kg
Dimension	126 (W) x 112.6(D) x 44.24 (H)mm
Operating	
Temperature	5°C~+50 °C (41 F~+122 F)

Dimension

