

4/9/16CH RealTime Standalone DVR

CX-M3204
CX-M3209
CX-M3216

Feature

- High level specification with elegant design and jog/shuttle
- Control recording resolution / quality / frame rate by each camera
- USB mouse supported
- LIVE screen editing / Digital zoom / call monitor supported
- Event / Panic / Schedule record / optimized record mode supported
- Diversified search by Time / Calendar / Event
- Diversified backup by USB2.0 and DVD-RW
- Convenient backup by AVI file
- Support DDNS / NTP / E-MAIL / CALLBACK functions
- DISK ID, S.M.A.R.T functions, Real-time disk health check
- Multi-Languages supported
- Intensive security function by chosen AUTHORITY
- Diversified network program by LIVE / SEARCH / PTZ / CMS / AGENT



Specification

Model	CX-M3204	CX-M3209	CX-M3216
System	NTSC / PAL Manual switch		
Input	4 / 9 / 16 CH input 1.0Vp-p, 75ohm unbalanced (BNC Type)		
Output	MainX1 / Call monitor X 1 / VGA	MainX1 / x call monitor X 2 / VGA / looping out x 9 / x 16	
S/N Ratio	More than 48dB		
Color	16.7 Million		
Monitoring Method			
Display Screen	1 / 4	1 / 4 / 9	1 / 4 / 9 / 16
Zoom	2 x 2 zoom for live		
Sequence Display	Available		
Display Resolution	NTSC:720(H)x 480(V) PAL: 720(H) x 576(V)	NTSC:720(H)x 480(V) PAL: 720(H) x 576(V)	NTSC:720(H)x 480(V) PAL: 720(H) x 576(V)
Recording / Play Function			
Recording Rate	D1: 120 / Half D1: 120 / CIF: 120 (NTSC) D1: 100 / Half D1: 100 / CIF: 100 (PAL)	D1: 120 / Half D1: 240 / CIF: 270 (NTSC) D1: 100 / Half D1: 200 / CIF: 225 (PAL)	D1: 120 / Half D1: 240 / CIF: 480 (NTSC) D1: 100 / Half D1: 200 / CIF: 400 (PAL)
Record Quality	Lowest / Low / Normal / High / Highest		
Compressed Mode	MPEG-4		
Recording Mode	Manual / Event(Motion detection, Alarm, Video loss) / Schedule		
Playback Mode	Time search / Event search / Play directly / Calendar		
Other Function			
Operation	Full Triplex		
Motion Detect	Area division: 12 x12, on/off sector selectable Sensitivity adjustment in 5 steps		
Network Function	TCP/IP with client software, IE (live view only)		
Alarm Function	4 alarm In / 1 alarm Out: NC / NO+COM	8 alarm In / 4 alarm Out: NC / NO+COM	16 alarm In / 4 alarm Out: NC / NO+COM
Backup	Flash (USB 2.0) / DVD-RW / CD-RW / Network		
RS485	PTZ Dome / Keyboard		
Storage	Internal: up to 4 HDD (4ch: up to 3 HDD)		
Audio	4 port input / 1 port output		
VGA Output	15 pins female D-SUB		
Mechanical			
IR Remote Controller	Standard		
Shuttle Control Input	X 1		
Power Supply	12V DC / 5A	100~240VAC / 4A	100~240VAC / 4A
Dimension	440(W) x 411.7(D) x 88(H) mm		
Operating Temperature	5°C~+40°C (41°F~+104°F)		
Operating Humidity	Less than 90%		

Dimension

