



COMMITTED TO XCELLENCE™



## PV5931T: 15" LCD TOUCH SCREEN 5-WIRE RESISTIVE TOUCH WITH USB INTERFACE

CTX PV5931T, the 15" LCD touch screen, incorporates industries fast responding and most reliable 5-wire resistive type touch panel to a high performing LCD monitor. It caters the need for all touch solutions such as POS, kiosks, ATM's Industrial controls etc. This monitor delivers very bright, sharper and fast response picture quality.

The display is featured with optional wall mounting. It has a very elegant and modern finish with black colored bezel with UL, cUL, CE, FCC & RoHS/WEEE safety certifications

### Features



### Specification Overview:

<b>Viewable Size:</b>	15" Diagonal
<b>Pixel Resolution:</b>	1024 x 768 Array Matrix
<b>Supported Colors:</b>	16.2 Million Colors
<b>Contrast Ratio:</b>	500 : 1, Typical
<b>Surface Brightness:</b>	300 nit (cd/m <sup>2</sup> ), Typical
<b>Viewing Angle (H/V):</b>	120° / 100° (CR:10), Typical
<b>Response Time:</b>	16ms, Typical
<b>Horizontal Scan:</b>	30KHz ~ 80KHz
<b>Vertical Refresh:</b>	59Hz ~ 75Hz
<b>Input Signals:</b>	RGB Analog, USB A male to B male, Stereo Audio
<b>Touch Interface:</b>	USB 2.0
<b>Speakers:</b>	1W x 2, Stereo
<b>Special Features:</b>	5-Wire Resistive Touch Screen USB interface
<b>Power Supply Input:</b>	Universal AC 100 ~ 240V (50/60Hz), Built-in
<b>Power Consumption:</b>	24 Watts (max.)
<b>Monitor Dimension:</b>	357 x 342 x 171 mm
<b>Net Weight/ Gross Weight:</b>	4.0 / 5.5Kgs
<b>Safety Regulations:</b>	UL, cUL, CE, FCC, RoHS, WEEE