



COMMITTED TO XCELLENCE™



PV5BT: 15" LCD TOUCH SCREEN 5-WIRE RESISTIVE TOUCH PANEL RS-232 INTERFACE

CTX PV5BT/ PV5BAT, the 15" LCD touch screen, incorporates industries fast responding and most reliable 5-wire resistive type touch panel to a high performing LCD monitor. It caters the need for all touch solutions such as POS, kiosks, ATM's Industrial controls etc. This monitor delivers very bright, sharper and fast response picture quality.

The display is featured with Pivot® Enabled and optional wall mounting. It has a very elegant and modern finish with black colored bezel with a 90° rotate-able base.

Features



Specification Overview:

Viewable Size:	15" Diagonal
Pixel Resolution:	1024 x 768 Array Matrix
Supported Colors:	16.2 Million Colors
Contrast Ratio:	400 : 1, Typical
Surface Brightness:	320 nit (cd/m ²), Typical
Viewing Angle (H/V):	140° / 125° (CR: 10), Typical
Response Time:	16ms, Typical
Horizontal Scan:	30KHz ~ 60KHz
Vertical Refresh:	59Hz ~ 75Hz
Input Signals:	RGB Analog, Touch Interface, Stereo Audio signal
Touch Interface:	RS-232 D-Sub to RJ-11
Speakers:	1W x 2, Stereo (PV5BAT only)
Special Features:	5-Wire Resistive Touch Screen, Pivot® Enabled
Power Supply Input:	Universal AC 100 ~ 240V (50/60Hz), Adapter
Power Consumption:	33 Watts (max.)
Monitor Dimension:	383 x 375 x 169 mm
Net Weight/ Gross Weight:	6.1 / 8.5Kgs
Safety Regulations:	CE, CB, UL, cUL, FCC, MPR II