

## PV9931T: 19" LCD TOUCH SCREEN

### 5-WIRE RESISTIVE TOUCH WITH RS-232 INTERFACE

CTX PV9931T, the 19" LCD touch screen, incorporates industries fast responding and most reliable 5-wire resistive type touch panel to a high performing LCD monitor. It caters the need for all touch solutions such as POS, kiosks, ATM's Industrial controls etc. This monitor delivers very bright, sharper and fast response picture quality.

The display is featured with optional wall mounting. It has a very elegant and modern finish with black colored bezel with UL, cUL, CE, FCC & RoHS/WEEE safety certifications



### Features



### Specification Overview:

<b>Viewable Size:</b>	19" Diagonal
<b>Pixel Resolution:</b>	1280 x 1024 Array Matrix
<b>Supported Colors:</b>	16.7 Million Colors
<b>Contrast Ratio:</b>	500 : 1, Typical
<b>Surface Brightness:</b>	300 nit (cd/m <sup>2</sup> ), Typical
<b>Viewing Angle (H/V):</b>	150° / 130° (CR:10), Typical
<b>Response Time:</b>	8ms, Typical
<b>Horizontal Scan:</b>	30KHz ~ 80KHz
<b>Vertical Refresh:</b>	56Hz ~ 75Hz
<b>Input Signals:</b>	RGB Analog, RS-232 to RJ-11, DVI-D, Stereo Audio
<b>Touch Interface:</b>	USB 2.0
<b>Speakers:</b>	1W x 2, Stereo
<b>Special Features:</b>	5-Wire Resistive Touch Panel RS-232 interface
<b>Power Supply Input:</b>	Universal AC 100 ~ 240V (50/60Hz), Built-in
<b>Power Consumption:</b>	35 Watts (max.)
<b>Monitor Dimension:</b>	422 x 418 x 235 mm
<b>Net Weight/ Gross Weight:</b>	5.0 / 6.3Kgs
<b>Safety Regulations:</b>	UL, cUL, CE, FCC