



S962A

PRICE-PERFORMANCE 19" LCD: DVI, SPEAKERS, STYLE AND HIGH SPECIFICATIONS

The S962A is the latest in high quality, well-priced products from CTX. Finished in silver and black to match the most modern, style-conscious, PCs and peripherals. This 19" LCD uses cutting edge MVA technology to improve picture quality but still manages to be one of the best priced 19" screens available.

The S962A has a remarkable contrast ratio of 700:1, ensuring the best possible picture for you. This is combined with a stylishly designed casing; 170° viewing angles, both vertically and horizontally; 25 ms response time and built-in stereo speakers.

The S962A is compatible with VESA wall-mounting standards and TCO'99 and ISO13406-2 certified.

| | |
|-------------------------------|---|
| Colour | Silver-Black |
| Size | 19" |
| Type | Active Matrix MVA TFT |
| Resolution | 1280x1024 array matrix (SXGA) |
| Colours | 16.7 million colours |
| Pixel Pitch | 0.294 mm / 0.294 mm pixel pitch |
| Contrast Ratio | 700:1, Typical |
| Brightness | 250 nit (cd/m ²), Typical |
| Horizontal Viewing Angle | 170°, Typical |
| Vertical Viewing Angle | 170°, Typical |
| Response Time | 25 ms, Typical |
| Horizontal Scan | 30kHz ~ 80kHz |
| Vertical Refresh | 59Hz ~ 75Hz |
| DVI | Yes |
| Recommended Resolution | 1280x1024 @ 60Hz |
| Plug & Play | VESA DDC 2B (VGA) / DDC 2B |
| Input Signals | RGB Video: Analog, 0.0 ~ 0.7 V Peak to Peak, Sync. Signal: Separate 3.3V and 5V TTLH/V Sync. |
| Input Connection | VGA 15 pin D-Sub |
| Speakers | Stereo, 2 x 1W, with Amplifier |
| Ear Phone Output | No |
| User Controls and Indicator | Front Panel Controls: Power Switch, LED Indicator, ESC, Up, Down, Enter On Screen Display Menu Controls: Contrast, Brightness, Volume, Auto Tune, Color Auto Color, Clock, Phase, H-Position, V-Position Smoothing, OSD Setting, Language, Reset, Source (D-15) |
| Security OSD Lock | Yes |
| VESA Wall Mount Compatible | Yes (100 mm) |
| Pivotable | No |
| Swivel Base | No |
| USB Hub | No |
| Power Supply | Built-In Power Supply |
| Input | Universal AC 100~240V (50~60Hz) |
| Power Consumption | 43 watt (max.) |
| Dimensions | |
| Monitor W x H x D w/base (mm) | 415x407.5x205 |
| Carton W x H x D (mm) | 482x560x138 |
| Weight | |
| N.W. / G.W. (kg) | 5.9 / 7.1 |
| Safety Regulations | UL, CUL, FCC, CE, TUV/GS, ISO13406-2, TCO '99 BSMI |

SEE MORE DETAILS



COMMITTED TO XCELLENCE

www.ctxme.com